

## PCB terminal block - MKDS 5/ 3-6,35 BK - 1714942

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB terminal block, nominal current: 32 A, rated voltage (III/2): 630 V, Nominal cross section: 4 mm<sup>2</sup>, pitch: 6.35 mm, number of positions: 3, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: black, Pin layout: Linear pinning, Solder pin [P]: 5.1 mm

The figure shows a 2-pos. version of the product

### Your advantages

- Well-known connection principle allows worldwide use
- Low temperature rise, thanks to maximum contact force
- Allows connection of two conductors
- The latching on the side enables various numbers of positions to be combined



### Key Commercial Data

|              |               |
|--------------|---------------|
| Packing unit | 50 pc         |
| GTIN         |               |
| GTIN         | 4017918257866 |

### Technical data

#### Item properties

|                           |                                      |
|---------------------------|--------------------------------------|
| Brief article description | PCB terminal block                   |
| Range of articles         | MKDS 5                               |
| Pitch                     | 6.35 mm                              |
| Number of positions       | 3                                    |
| Connection method         | Screw connection with tension sleeve |
| Drive form screw head     | Slotted                              |
| Screw thread              | M3                                   |
| Mounting type             | Wave soldering                       |
| Pin layout                | Linear pinning                       |
| Number of levels          | 1                                    |
| Number of connections     | 3                                    |

# PCB terminal block - MKDS 5/ 3-6,35 BK - 1714942

## Technical data

### Item properties

|                      |   |
|----------------------|---|
| Number of potentials | 3 |
|----------------------|---|

### Electrical parameters

|              |       |
|--------------|-------|
| Nom. voltage | 630 V |
|--------------|-------|

### Connection capacity

|  |   |
|--|---|
| Connection method  | Screw connection with tension sleeve          |
| pluggable  | Yes   |
| Conductor cross section solid  | 0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>     |
| Conductor cross section flexible   | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>     |
| Conductor cross section AWG / kcmil  | 24 ... 10                                     |
| Conductor cross section flexible, with ferrule without plastic sleeve                  | 0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>    |
| Conductor cross section, flexible, with ferrule, with plastic sleeve                   | 0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>    |
| 2 conductors with same cross section, solid  | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>   |
| 2 conductors with same cross section, flexible   | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>   |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve        | 0.25 mm <sup>2</sup> ... 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>   |
| Stripping length   | 8 mm  |
| Torque   | 0.5 Nm ... 0.6 Nm                             |

### Material data - contact

|  |   |
|--|---|
| Note                                     | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/ JEDEC JESD 201 |
| Contact material                         | Cu alloy  |
| Surface characteristics                  | Tin-plated  |
| Metal surface terminal point (top layer) | Tin (4 - 8 µm Sn)   |
| Metal surface soldering area (top layer) | Tin (4 - 8 µm Sn)   |

### Material data - housing

|   |        |
|---|--------|
| Insulating material   | PA     |
| Insulating material group   | I      |
| CTI according to IEC 60112  | 600    |
| Flammability rating according to UL 94                            | V0     |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850    |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775    |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C |

### Dimensions for the product

|              |   |
|--------------|---|
| Caption      | Schematic representation – for additional information, see product range drawing in the Download Center |
| Length [ l ] | 12.5 mm   |
| Width [ w ]  | 19.05 mm  |
| Height [ h ] | 26.6 mm   |

# PCB terminal block - MKDS 5/ 3-6,35 BK - 1714942

## Technical data

### Dimensions for the product

|                             |              |
|-----------------------------|--------------|
| Pitch                       | 6.35 mm      |
| Height (without solder pin) | 21.5 mm      |
| Solder pin [P]              | 5.1 mm       |
| Pin dimensions              | 0.9 x 0.9 mm |
| Dimension a                 | 12.7 mm      |

### Dimensions for PCB design

|               |        |
|---------------|--------|
| Hole diameter | 1.3 mm |
|---------------|--------|

### Packaging information

|                            |                     |
|----------------------------|---------------------|
| Type of packaging          | packed in cardboard |
| Pieces per package         | 50                  |
| Denomination packing units | Pcs.                |

### General product information

|              |  |
|--------------|--|
| Type of note | Note on application  |
| Note         | For safe conductor connection, always adhere to a defined tightening torque. Particularly in the case of PCB terminal blocks with two or three positions, the individual solder pin for each contact point cannot compensate for this. That is why the terminal blocks must be supported during conductor connection (held with one hand, support on the housing). |

### Ambient conditions

|   |   |
|---|---|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C  |
| Ambient temperature (assembly)          | -5 °C ... 100 °C  |
| Ambient temperature (operation)         | -40 °C ... 100 °C (Depending on the current carrying capacity/derating curve) |

### Termination and connection method

|  |                       |
|--|-----------------------|
| Test for conductor damage and slackening | IEC 60998-2-1:1990-04 |
|  | Test passed           |

### Pull-out test

|  |   |
|--|---|
| Pull-out test  | IEC 60998-2-1:1990-04                   |
|  | Test passed                             |
| Conductor cross section / conductor type / tensile force | 0.2 mm <sup>2</sup> / solid / > 10 N    |
|  | 0.2 mm <sup>2</sup> / flexible / > 10 N |
|  | 6 mm <sup>2</sup> / solid / > 80 N      |
|  | 4 mm <sup>2</sup> / flexible / > 60 N   |

### Electrical tests

|                             |                   |
|-----------------------------|-------------------|
| Rated current               | 32 A              |
| Conductor cross section     | 4 mm <sup>2</sup> |
| Rated voltage (III/2)       | 630 V             |
| Rated surge voltage (III/2) | 6 kV              |

# PCB terminal block - MKDS 5/ 3-6,35 BK - 1714942

## Technical data

### Air clearances and creepage distances

|   |   |
|---|---|
| Clearances and creepage distances               | IEC 60664-1:2007-04                                 |
| Specification                                   | IEC 60664-1:2007-04                                 |
| Rated insulation voltage (III/3)                | 500 V   |
| Rated insulation voltage (III/2)                | 630 V   |
| Rated insulation voltage (II/2)                 | 1000 V  |
| Rated surge voltage (III/3)                     | 6 kV  |
| Rated surge voltage (III/2)                     | 6 kV  |
| Rated surge voltage (II/2)                      | 6 kV  |
| Minimum clearance - inhomogeneous field (III/3) | 5.5 mm  |
| Minimum clearance - inhomogeneous field (III/2) | 5.5 mm  |
| Minimum clearance - inhomogeneous field (II/2)  | 5.5 mm  |
| Minimum creepage distance value (III/3)         | 6.3 mm  |
| Minimum creepage distance value (III/2)         | 5.5 mm  |
| Minimum creepage distance value (II/2)          | 5.5 mm  |
| Note on connection cross section                | With connected conductor 6 mm <sup>2</sup> (solid). |

### Vibration test

|                        |                        |
|------------------------|------------------------|
| Specification          | IEC 60068-2-6:1995-03  |
| Result                 | Test passed            |
| Frequency              | 10 - 150 - 10 Hz       |
| Sweep speed            | 1 octave/min           |
| Amplitude              | 0.35 mm (10 - 60.1 Hz) |
| Acceleration           | 5 g (60.1 - 150 Hz)    |
| Test duration per axis | 2.5 h                  |

### Resistance to ageing, humidity and penetration of solids

|            |                |
|------------|----------------|
| Dry heat   | 168 h/100°C    |
| Humid heat | 48 h/25 °C/92% |

### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|                                  | CSA    |


### Environmental Product Compliance

|            |   |
|------------|---|
| REACH SVHC | Lead 7439-92-1  |
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

# PCB terminal block - MKDS 5/ 3-6,35 BK - 1714942

Diagram



Type: MKDS 5/2-6,35 and MKDS 5/3-6,35  
 Test following DIN EN 60512-5-2:2003-01  
 Reduction factor = 1  
 No. of positions: 5

## Approvals

Approvals

Approvals

DNV GL / CSA / RS / CCA / SEV / EAC / cULus Recognized

Ex Approvals

## Approval details

|        |  |   |            |
|--------|--|---|------------|
| DNV GL |  | <a href="https://approvalfinder.dnvgl.com/">https://approvalfinder.dnvgl.com/</a> | TAE00001EV |
|--------|--|---|------------|

|     |  |   |       |
|-----|--|---|-------|
| CSA |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
|-----|--|---|-------|

|                    |       |       |
|--------------------|-------|-------|
|                    | B     | D     |
| Nominal voltage UN | 300 V | 300 V |


## PCB terminal block - MKDS 5/ 3-6,35 BK - 1714942


### Approvals


|                            | B     | D     |
|----------------------------|-------|-------|
| Nominal current IN         | 10 A  | 10 A  |
| mm <sup>2</sup> /AWG/kcmil | 28-10 | 28-10 |

|    |   |   |              |
|----|---|---|--------------|
| RS |  | <a href="http://www.rs-head.spb.ru/en/index.php">http://www.rs-head.spb.ru/en/index.php</a> | 17.00014.272 |
|----|---|---|--------------|

|                            |         |  |
|----------------------------|---------|--|
| CCA                        | IK-3249 |  |
| Nominal voltage UN         | 450 V   |  |
| mm <sup>2</sup> /AWG/kcmil | 4       |  |

|                            |   |   |         |
|----------------------------|---|---|---------|
| SEV                        |  | <a href="https://www.electrosuisse.ch/de/meta/shop/produktzertifikate.html">https://www.electrosuisse.ch/de/meta/shop/produktzertifikate.html</a> | IK-4199 |
| Nominal voltage UN         | 450 V   |   |         |
| Nominal current IN         | 32 A  |   |         |
| mm <sup>2</sup> /AWG/kcmil | 4   |   |         |

|     |   |         |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

| cULus Recognized           |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19770427 |
|----------------------------|---|---|-----------------|
|                            | B   | D   |                 |
| Nominal voltage UN         | 300 V   | 300 V   |                 |
| Nominal current IN         | 30 A  | 10 A  |                 |
| mm <sup>2</sup> /AWG/kcmil | 30-10   | 30-10   |                 |

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
 Flachsmarktstr. 8  
 32825 Blomberg  
 Germany  
 Tel. +49 5235 300  
 Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>