

## High Voltage Rectifiers - Formed Lead

0.8A - 3.5A • 30ns - 70ns • Hermetic

ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS												
Part Number	Working Reverse Voltage (V <sub>rwm</sub> )	Average Rectified Current (I <sub>o</sub> )		Reverse Current @ V <sub>rwm</sub> (I <sub>r</sub> )		Forward Voltage (V <sub>f</sub> )		1 Cycle Surge Current tp=8.3ms (I <sub>fsm</sub> )	Repetitive Surge Current (I <sub>frm</sub> )	Reverse Recovery Time (3) (T <sub>rr</sub> )	Thermal Impd. θ <sub>J-C</sub>	Junction Cap. @50VDC @1kHz (C <sub>j</sub> )
		55°C(1)	100°C(2)	25°C	100°C	25°C		25°C	25°C	25°C	25°C	25°C
	Volts	Amps	Amps	µA	µA	Volts	Amps	Amps	Amps	ns	°C/W	pF
Z20FF3LL Z50FF3LL	2000 5000	2.0 0.8	1.2 0.4	1.0 1.0	25 25	6.0 12.5	0.75 0.36	65 22	10 4	30 30	5.0 5.0	20 16
Z20FF5LL Z50FF5LL	2000 5000	2.0 0.8	1.2 0.4	1.0 1.0	25 25	6.0 12.5	0.75 0.36	65 22	10 4	50 50	5.0 5.0	20 16
1N6513LL 1N6515LL 1N6517LL	2000 3000 5000	3.5 2.5 1.5	2.4 1.5 1.0	1.0 1.0 1.0	25 25 25	3.5 6.0 8.0	2.0 1.5 1.0	100 60 40	15 10 8	70 70 70	5.0 5.0 5.0	25 20 16

(1)TC=55°C (2)TC=100°C (3)I<sub>f</sub>=0.5A, I<sub>r</sub>=1.0A, I<sub>rr</sub>=0.25A \*Op. Temp.= -65°C to +175°C Stg. Temp.= -65°C to +200°C



Part	A	B
Z20FF3LL	.350(8.89) MAX.	.220
Z20FF5LL	.320(8.13) MIN.	(5.59)
Z50FF3LL	.390(9.91) MAX.	.260
Z50FF5LL	.350(8.89) MIN.	(6.60)
1N6513LL	.340(8.64) MAX.	.210
1N6515LL	.320(8.13) MIN.	(5.33)
1N6515LL	.360(9.14) MAX.	.230
1N6515LL	.340(8.64) MIN.	(5.84)
1N6517LL	.380(9.65) MAX.	.250
1N6517LL	.350(8.89) MIN.	(6.35)

