

*New Jersey Semi-Conductor Products, Inc.*

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.

TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960  
**2SC4510**

**Silicon NPN Power Transistor****DESCRIPTION**

- High Collector-Emitter Sustaining Voltage-  
:  $V_{CEO(SUS)} = 400V(\text{Min.})$
- High Switching Speed
- High Reliability
- Low Collector Saturation Voltage

**APPLICATIONS**



- Switching regulators
- DC-DC converter
- Solid state relay
- General purpose power amplifiers

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	500	V
$V_{CEO}$	Collector-Emitter Voltage	400	V
$V_{EBO}$	Emitter-Base voltage	10	V
$I_C$	Collector Current-Continuous	15	A
$I_B$	Base Current-Continuous	5	A
$P_C$	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	80	W
$T_J$	Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-55~150	$^\circ\text{C}$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th-j-c}$	Thermal Resistance, Junction to Case	1.56	$^\circ\text{C/W}$



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

## Silicon NPN Power Transistor

2SC4510

## ELECTRICAL CHARACTERISTICS

 $T_c=25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=0.2\text{A}; I_B=0$	400			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	$I_C=1\text{mA}; I_E=0$	500			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E=1\text{mA}; I_C=0$	10			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=6\text{A}; I_B=1.2\text{A}$			0.8	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=6\text{A}; I_B=1.2\text{A}$			1.2	V
$I_{CBO}$	Collector Cutoff Current	$V_{CB}=450\text{V}; I_E=0$			0.1	mA
$I_{EBO}$	Emitter Cutoff Current	$V_{EB}=10\text{V}; I_C=0$			0.1	mA
$h_{FE}$	DC Current Gain	$I_C=2\text{A}; V_{CE}=5\text{V}$	25		65	

## Switching times

$t_{on}$	Turn-on Time	$I_C=7.5\text{A}; I_{B1}=0.75\text{A}; I_{B2}=-1.5\text{A};$ $R_L=20\Omega; P_W=20\mu\text{s};$ Duty Cycle $\leq 2\%$			1.0	$\mu\text{s}$
$t_{stg}$	Storage Time				2.5	$\mu\text{s}$
$t_f$	Fall Time				0.5	$\mu\text{s}$