

TOSHIBA TRANSISTOR SILICON NPN EPITAXIAL TYPE

# 2SD2127


SWITCHING APPLICATIONS

LAMP, SOLENOID DRIVE APPLICATIONS.

- High DC Current Gain :  $h_{FE} = 500 \sim 1500$
- Low Collector Saturation Voltage :  $V_{CE(sat)} = 0.3V$  (Max.)
- Zener Diode Included Between Collector and Base.


MAXIMUM RATINGS ( $T_a = 25^\circ C$ )

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	$V_{CBO}$	$60 \pm 10$	V
Collector-Emitter Voltage	$V_{CEO}$	$60 \pm 10$	V
Emitter-Base Voltage	$V_{EBO}$	7	V
Collector Current	DC	$I_C$	3
	Pulse	$I_{CP}$	5
Base Current	$I_B$	1	A
Collector Power Dissipation	$T_a = 25^\circ C$	$P_C$	2.0
	$T_c = 25^\circ C$		25
Junction Temperature	$T_j$	150	$^\circ C$
Storage Temperature Range	$T_{stg}$	$-55 \sim 150$	$^\circ C$



Weight : 1.7g (Typ.)

EQUIVALENT CIRCUIT



961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT				
Collector Cut-off Current	$I_{CBO}$	$V_{CB} = 45V, I_E = 0$	—	—	10	$\mu A$				
Emitter Cut-off Current	$I_{EBO}$	$V_{EB} = 7V, I_C = 0$	—	—	10	$\mu A$				
Collector-Emitter Breakdown Voltage	$V_{(BR) CEO}$	$I_C = 50mA, I_B = 0$	50	60	70	V				
DC Current Gain	$h_{FE} (1)$	$V_{CE} = 1V, I_C = 0.5A$	500	—	1500					
	$h_{FE} (2)$	$V_{CE} = 1V, I_C = 1A$	150	—	—					
Collector-Emitter Saturation Voltage	$V_{CE} (sat)$	$I_C = 1A, I_B = 10mA$	—	—	0.3	V				
Base-Emitter Saturation Voltage	$V_{BE} (sat)$	$I_C = 1A, I_B = 10mA$	—	—	1.2	V				
Emitter-Collector Forward Voltage	$V_{ECF}$	$I_E = 1A, I_B = 0$	—	—	2.0	V				
Transition Frequency	$f_T$	$V_{CE} = 5V, I_C = 0.5A$	—	140	—	MHz				
Collector Output Capacitance	$C_{ob}$	$V_{CB} = 10V, I_E = 0, f = 1MHz$	—	30	—	pF				
Switching Time	Turn-on Time	$t_{on}$					—	0.6	—	$\mu s$
	Storage Time	$t_{stg}$					—	1.6	—	
	Fall Time	$t_f$					$I_{B1} = -I_{B2} = 10mA,$ $DUTY CYCLE \leq 1%$ $V_{CC} \cong 30V$	—	0.4	

