
PNP TRANSISTOR**A733****-100mA**



- AF OUTPUT AMPLIFIER

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (Ta=25)

PARAMETERS	SYMBOL	MIN	TYP	MAX	UNIT	CONDITION
Collector-Emitter Breakdown Voltage	BV _{ceo}	-50			V	I _c =1mA
Collector-Base Breakdown Voltage	BV _{cb0}	-60			V	I _c =5 μ A
Emitter-Base Breakdown Voltage	BV _{eb0}	-5			V	I _e =50 μ A
Collector-Base Leakage	I _{cbo}			-0.1	μ A	V _{cb} =-60V
Emitter-Base Leakage	I _{ebo}			-0.1	μ A	V _{eb} =-5V
Collector-Emitter Saturation Voltage	V _{ce (sat)}		-0.18	-0.3	V	I _c =-100mA, I _b =-10mA
DC Current Gain	H _{fe}	90	200	600		V _{ce} =-6.0V, I _c =-1.0mA
Collector Current	I _c		-100		mA	
Current Gain Bandwidth	f _r	100	180		MHz	V _{ce} =-6V, I _e =10mA
Output Capacitance	C _{ob}		4.5	6.0	pF	V _{cb} =-10V, I _e =0, f=1MHz
Power Dissipation	P _c			0.25	W	
Junction Temperature	T _j			125		
Storage Temperature	T _{stg}	-55		125		

Classification of Hfe

Rank	R	Q	P	K
Range	90-180	135-270	200-400	300-600

**STANSON TECHNOLOGY**

120 Bentley Square, Mountain View, Ca 94040 USA

TEL: (650) 9389294 FAX: (650) 9389295