
# 32.768kHz SMD LOW PROFILE CRYSTAL

ABS06





#### **FEATURES:**

- Smallest industry package size for 32.768kHz crystals
- 0.6mm height ideal for high density circuit boards
- Ceramic package offers excellent environmental & heat resistance
- Extended temperature -40°C to +85°C for industrial applications


#### **APPLICATIONS:**

- Wide range in communication & measuring equipment
- Commercial & Industrial applications
- Automotive electronics applications
- Wireless communications
- PDA and Palm Pilots


### **STANDARD SPECIFICATIONS:**

PARAMETERS	
ABRACON P/N	ABS06 Series
Nominal Frequency	32.768 kHz
Operating Temperature	-40°C to + 85°C
Turn-over Temperature	+25°C to ±5°C
Storage Temperature	-55°C to +125°C
Frequency Tolerance	±20 ppm max.
Temperature Coefficient	- 0.034±0.005 ppm/°C2
Equivalent Series Resistance	90 kohms max.
Load Capacitance CL	12.5 pF (see option)
Drive Level	0.5 μW max.
Aging (first year) 25°C	± 3 ppm max.
Insulation Resistance	500 MΩ with 100 Vdc ±15V

## EXAMPLE TUNING FORK CRYSTAL TEMPERATURE CURVE



#### > OPTIONS AND PART IDENTIFICATION:



<sup>\*</sup>Contact ABRACON for non-standard load capacitance.




# 32.768kHz SMD LOW PROFILE CRYSTAL

ABS06







#### **OUTLINE DRAWING:**



#### TAPE & REEL: T = Tape and reel 3,000pcs/reel



### > TAPE & REEL:





Need a test socket for the ABS06 Series? To view compatible **PRECISION TEST & BURN-IN SOCKETS** for these parts, **click here. P/N AXS-2012-02-04** 

**NOTE**: Abracon manufactured products are intended for general commercial and industrial use. For applications requiring high reliability and/or presenting extreme operating environment, written consent & authorization from Abracon is required.



