

3469674 FAIRCHILD SEMICONDUCTOR

84D 27294 D1

FAIRCHILD

A Schlumberger Company

BAX16

General Purpose Industrial Diode

T-01-09

- BV... 180 V (MIN) @ 100 μ A
- I_R... 100 nA (MAX) @ 150V

PACKAGE

BAX16

DO-35

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures

| | |
|--|-----------------|
| Storage Temperature Range | -65°C to +200°C |
| Maximum Junction Operating Temperature | +175°C |
| Lead Temperature | +260°C |

Power Dissipation (Note 2)

| | |
|---|------------|
| Maximum Total Power Dissipation at 25°C Ambient | 500 mW |
| Linear Power Derating Factor (from 25°C) | 3.33 mW/°C |

Maximum Voltage and Currents

| | | |
|-----------------------|---------------------------------|--------|
| WIV | Working Inverse Voltage | 150 V |
| I _O | Average Rectified Current | 200 mA |
| I _F | Continuous Forward Current | 500 mA |
| I _f | Peak Repetitive Forward Current | 600 mA |
| I _{f(surge)} | Peak Forward Surge Current | |
| | Pulse Width = 1 s | 1.0 A |
| | Pulse Width = 1 μ s | 4.0 A |

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

| SYMBOL | CHARACTERISTIC | MIN | MAX | UNITS | TEST CONDITIONS |
|-----------------|--------------------------------|-----|------|---------|---|
| V _F | Forward Voltage | | 1.5 | V | I _F = 200 mA |
| | | | 1.4 | V | I _F = 200 mA, T _A = 175°C |
| | | | 1.3 | V | I _F = 100 mA |
| | | | 0.85 | V | I _F = 10 mA, T _A = 100°C |
| | | | 0.65 | V | I _F = 1 mA |
| I _R | Reverse Current | | 100 | nA | V _R = 150 V |
| | | | 100 | μ A | V _R = 150 V, T _A = 150°C |
| | | | 25 | nA | V _R = 50 V |
| | | | 25 | μ A | V _R = 50 V, T _A = 150°C |
| BV | Breakdown Voltage | 180 | | V | I _R = 100 μ A |
| C | Capacitance | | 10 | pf | V _R = 0, f = 1 MHz |
| t _{rr} | Reverse Recovery Time (Note 3) | | 120 | ns | I _F = 30 mA, I _R = 30 mA R _L = 100 Ω |
| Q _s | Stored Charge | | 700 | pC | I _F = 10 mA, V _R = 5 V R _L = 500 Ω |

NOTES:

1. These ratings are limiting values above which the serviceability of the diode may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty-cycle operation.
3. Recovery to I_R = 3 mA.
4. For product family characteristic curves, refer to Chapter 4, D1.