

**DESCRIPTION**

- Collector–Emitter Sustaining Voltage  
:  $V_{CEO(SUS)} = 450V(\text{Min.})$
- Collector Saturation Voltage  
:  $V_{CE(sat)} = 0.5V(\text{Max}) @ I_C = 1.0A$
- Very High Switching Speed

**APPLICATIONS**



- Designed for use in lighting applications and low cost switch-mode power supplies

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CES}$	Collector-Emitter Voltage	800	V
$V_{CEO}$	Collector-Emitter Voltage	450	V
$V_{EBO}$	Emitter-Base Voltage	9	V
$I_C$	Collector Current-Continuous	5	A
$I_{CM}$	Collector Current-peak $t_p < 5\text{ms}$	10	A
$I_B$	Base Current-Continuous	2	A
$I_{BM}$	Base Current-peak $t_p < 5\text{ms}$	4	A
$P_C$	Collector Power Dissipation $T_C=25^\circ\text{C}$	80	W
$T_i$	Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-65~150	$^\circ\text{C}$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.56	$^\circ\text{C/W}$
$R_{th\ j-A}$	Thermal Resistance, Junction to Ambient	62.5	$^\circ\text{C/W}$



**ELECTRICAL CHARACTERISTICS**

$T_C = 25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CE0(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C = 50\text{mA}; I_B = 0$	450			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E = 10\text{mA}; I_C = 0$	9			V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C = 1\text{A}; I_B = 0.2\text{A}$			0.5	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C = 2\text{A}; I_B = 0.4\text{A}$			0.7	V
$V_{CE(sat)-3}$	Collector-Emitter Saturation Voltage	$I_C = 4\text{A}; I_B = 0.75\text{A}$			1.1	V
$V_{BE(sat)-1}$	Base-Emitter Saturation Voltage	$I_C = 1\text{A}; I_B = 0.2\text{A}$			1.1	V
$V_{BE(sat)-2}$	Base-Emitter Saturation Voltage	$I_C = 2\text{A}; I_B = 0.4\text{A}$			1.2	V
$I_{CES}$	Collector Cutoff Current	$V_{CE} = 800\text{V}; V_{BE} = 0$ $V_{CE} = 800\text{V}; V_{BE} = 0, T_C = 125^\circ\text{C}$			0.1 0.5	mA
$I_{CEO}$	Collector Cutoff Current	$V_{CE} = 450\text{V}; I_B = 0$			0.25	mA
$h_{FE-1}$	DC Current Gain	$I_C = 10\text{mA}; V_{CE} = 5\text{V}$	10			
$h_{FE-2}$	DC Current Gain	$I_C = 0.5\text{A}; V_{CE} = 5\text{V}$			60	
$h_{FE-3}$	DC Current Gain	$I_C = 2\text{A}; V_{CE} = 5\text{V}$	13		32	
$V_F$	Diode Forward Voltage	$I_F = 2\text{A}$			1.5	V

Switching Times, Resistive Load

$t_s$	Storage Time	$I_C = 2.5\text{A}; I_{B1} = -I_{B2} = 0.5\text{A};$ $V_{CC} = 150\text{V}; t_p = 30 \mu\text{s}$			2.2	$\mu\text{s}$
$t_f$	Fall Time				0.8	$\mu\text{s}$

◆  **$h_{FE-3}$  Classifications**

A	B
13-23	22-32