

Features

- DC restore and sync separator
- Wideband (100MHz) DC restore
- Advanced sync separator
- Programmable data slicer
- Single 5 volt operation
- Differential Gain = 0.1%
- Differential Phase = 0.1°
- Low power (<75mW)

Applications

- Video Capture & Editing
- Video Projectors
- Set Top Boxes
- Security Video
- Embedded data recovery

Ordering Information

Part No.	Temp. Range	Package	Outline #
EL4501CS	-40°C to +85°C	24-Pin SOIC	MDP0027
EL4501CU	-40°C to +85°C	24-Pin QSOP	MDP0031


General Description

The EL4501C Video Front End (VFE) is an integrated solution that provides the key analog signal conditioning functions for analog video signals. It forms the front end interface for either an analog or analog/digital video system. The VFE contains a high bandwidth DC Restore, a sophisticated Sync Separator, and a Data Slicer for embedded data recovery.

The VFE will perform the restoration of the DC reference level (blanking level) and the extraction of all of the necessary timing signals needed for synchronization and control. The sync separator is designed for very good noise immunity by incorporating a signal qualification scheme and internal brick wall filter. A data slicer is also included to help decode data embedded in the active video or VBI areas of the signal.

The VFE operates from a single 5 volt supply and is available in a small 24 pin QSOP package that takes only 0.08in²(54mm²) of board area, as well as a standard 24 pin SOIC.

Connection Diagram



EL4501C - Preliminary

Video Front End

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$)

Values beyond absolute maximum ratings can cause the device to be prematurely damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

Supply Voltage (V_S to GND) +6V
Input Voltage GND - 0.3V, V_S +0.3V

Storage Temperature Range -65°C to +150°C
Ambient Operating Temperature -40°C to +85°C
Operating Junction Temperature 125°C
Power Dissipation See Curves

Important Note:

All parameters having Min/Max specifications are guaranteed. Typ values are for information purposes only. Unless otherwise noted, all tests are at the specified temperature and are pulsed tests, therefore: $T_J = T_C = T_A$.

Electrical Characteristics

$V_S = +5\text{V}$, $\text{GND} = 0\text{V}$, $T_A = 25^\circ\text{C}$, Input Video = 1V_{P-P} unless otherwise specified.

Parameter	Description	Conditions	Min	Typ	Max	Unit
I_S	Supply Current	No Load, $V_{IN} = 0\text{V}$			20	mA
Video Amplifier Section						
V_{OP}	Positive Output Voltage Swing	$R_L = 150\Omega$ to $V_{S/2}$	4.70	4.85		V
		$R_L = 150\Omega$ to GND	4.20	4.60		V
		$R_L = 1\text{k}$ to $V_{S/2}$	4.95	4.97		V
V_{ON}	Negative Output Voltage Swing	$R_L = 150\Omega$ to $V_{S/2}$		0.15	0.30	V
		$R_L = 150\Omega$ to GND		0		V
		$R_L = 1\text{k}$ to $V_{S/2}$		0.03	0.05	V
$+I_{OUT}$	Positive Output Current	$R_L = 10\Omega$ to $V_{S/2}$	60	80	120	mA
$-I_{OUT}$	Negative Output Current	$R_L = 10\Omega$ to $V_{S/2}$	-50	-60	-80	mA
dG	Differential Gain Error ^[1]	Standard NTSC test, $A_V = 2$, $R_L = 150\Omega$		0.1		%
dP	Differential Phase Error ^[1]	Standard NTSC test, $A_V = 2$, $R_L = 150\Omega$		0.1		°
BW	Bandwidth	-3dB, $G = 1$, $R_L = 10\text{k}\Omega$ to GND		100		MHz
		-3dB, $G = 1$, $R_L = 150\Omega$ to GND		60		MHz
BW1	Bandwidth	+/-0.1dB, $G = 2$, $R_L = 150\Omega$ to GND		8		MHz
SR	Slew Rate	25% to 75%, 3.5V _{P-P} , $R_L = 150\Omega$	150	200		V/ μs
V_{RL}	Ref Level Range		0		3.5	V
t_s	Settling Time	to 0.1%, $V_{IN} = 0\text{V}$ to 3V		35		ns
R_{IN}	Input Resistance (VIDEO_IN)		90	115	140	k Ω
C_{IN}	Input Capacitance (VIDEO_IN)			1.5		pF
A_{VOL}	Open Loop Voltage Gain	$R_L = \text{no load}$, $V_{OUT} = 0.5\text{V}$ to 3V	54	65		dB
		$R_L = 150\Omega$ to GND, $V_{OUT} = 0.5\text{V}$ to 3V	40	50		dB
DC Restore Section						
CMIR	Common Mode Input Range (REF_IN)	CMRR \geq TBD dB	0		3.5	V
V_{OS}	Input Offset Voltage	DC restored	-20		+20	mV
TCV _{OS}	Input Offset Voltage Temperature Coefficient			10		$\mu\text{V}/^\circ\text{C}$
I_B	Input Bias Current (REF_IN)	$V_{CM} = 0\text{V}$ to 3.5V		1	100	nA
Data Slicer Section						
I_{IH}	Input High Current (DS_MODE & DS_ENAB)	$V_{IH} = 5\text{V}$		4	6	μA
I_{IL}	Input Low Current (DS_MODE & DS_ENAB)	$V_{IL} = 0\text{V}$		1	100	nA
V_{IH}	Input High Voltage (DS_MODE & DS_ENAB)		4.5			V
V_{IL}	Input Low Voltage (DS_MODE & DS_ENAB)				0.5	V
V_{OH}	Output High Voltage (DS_OUT)	$I_{OUT} = -1\text{mA}$	4.75	4.9		V
V_{OL}	Output Low Voltage (DS_OUT)	$I_{OUT} = 1\text{mA}$		0.1	0.25	V
I_{OUT}	Short Circuit Current (DS_OUT)	$R_L = 10\Omega$ to 2.5V	15	20		mA

EL4501C - Preliminary

Video Front End

Electrical Characteristics

$V_S = +5V$, $GND = 0V$, $T_A = 25^\circ C$, Input Video = $1V_{p-p}$ unless otherwise specified.

Parameter	Description	Conditions	Min	Typ	Max	Unit
I_B	Input Bias Current (DS_REF)	DS_REF = 0V & 5V	-100	1	100	nA
V_{OS}	Input Offset Voltage		-20		+20	mV
V_{HYS}	Hysteresis			10	15	mV
t_{PD}	Propagation Delay	50% to 50%		18	28	ns
$t_{R/F}$	Rise/Fall Time	10% to 90%, $R_L = 150k$, $C_L = 5pF$		1.2	1.8	ns
Sync Separator Section						
V_{OH}	Output High Voltage	$I_{OH} = -1.6mA$	4.6			V
V_{OL}	Output Low Voltage	$I_{OL} = 1.6mA$			0.4	V
V_{THSRH}	Slicing Level		45	50	55	%
T_{CD}	Composite Sync Delay	With Filter	TBD		TBD	
T_{CD}	Composite Sync Delay	Without Filter	TBD		TBD	
V_{SR}	Sync In Reference Level			1.5		V
R_{INSR}	Sync Reference Input Impedance			90		k Ω
V_{RANGE}	Input Dynamic Range		0.5		2.0	V_{p-p}
t_{CD}	Comp Sync Delay	From 50% point of leading edge of sync	50	75	100	ns
t_{BD}	Back Porch Delay	From 50% point of trailing edge of sync	340	430	520	ns
t_{BW}	Back Porch Width		2.7	3.0	3.3	μs
t_{HD}	Horiz Sync Delay	From 50% point of leading edge of sync	350	450	550	ns
t_{HW}	Horiz Sync Width		3.7	4.7	5.7	μs
t_{VW}	Vert Sync Width	Serrations	185	195	205	μs
t_{VDD}	Vert Sync Default Delay	No serrations	51	63.5	76	μs
f_H	Horiz Scan Rate	$R_{FREQ} = xx$ to yy k Ω	15		130	kHz
V_{LOS}	LOS Detect Threshold	Compared to Sync Tip Amplitude		72		mV
t_{JIT}	Output Jitter	All sync separator outputs			5	ns
Reference Section						
V_{REF}	Reference Output Voltage (REF_OUT)	$I_{OUT} = +2mA$ to $-0.5mA$	1.2	1.3	1.4	V


EL4501C - Preliminary

Video Front End

Typical Performance Curves

CONFIDENTIAL


Timing Diagrams



EL4501C - Preliminary

Video Front End

Timing Diagrams (cont.)




Pin Description

Pin Number	Pin Name	Pin Type	Pin Description
1	VFB	Input	Connection for gain and feedback resistors, R_F and R_G .
2	VIDEO_IN	Input	Input to DC restore amplifier. Input coupling capacitor connects from here to video source.
3	DS_MODE	Input	Sets the mode of the DS comparator. Logic high selects a standard logic output. Logic low selects an open drain/collector.
4	DS_ENAB	Input	Enables the output of the comparator. A logic high enables the comparator. A logic low tri-states it.
5	GND	Input	Analog ground.
6	GND _D	Input	Digital ground
7	R _{FREQ}	Input	Connection for bias resistor that sets the overall timing.
8	FSEL	Input	Enable/ bypass internal brick wall filter. A logic high is used to enable the filter, a logic low to disable it.
9	SYNC_IN	Input	Input to the sync separator. Connects to the video source via a coupling capacitor, or to a color burst input filter.
10	LOS	Output	Loss of signal output. Goes high if no input video signal is detected.
11	COMPOSITE	Output	Composite sync output.
12	HORIZONTAL	Output	Horizontal sync output.
13	VERTICAL	Output	Vertical sync output.
14	ODD/EVEN	Output	Odd/Even field indicator output.
15	BACK_PORCH	Output	Back porch output.
17	SYNC_AMP	Output	Amplitude of sync tip. Can be used to control AGC circuit.
18	V _{SD}	Input	Digital power supply. Nominally +5V.
19	V _S	Input	Analog power supply. Nominally +5V.
20	REF-OUT	Output	Voltage reference for use as blanking level in low cost system
21	REF_IN	Input	Dc voltage on this pin sets the DC restore voltage and output blanking level.
22	DS_REF	Input	Sets the slicing level or reference level for the comparator.
23	DS_OUT	Output	Output of the data slicing comparator. The output is either open drain/collector or standard symmetrical logic depending on the DS_MODE pin.
24	VIDEO_OUT	Output	Output of DC restore amplifier.

EL4501C - Preliminary

Video Front End

Block Diagram



Description of Operation

The EL4501C incorporates the following functional blocks:

- DC restore amplifier
- Advanced sync separator
- Data Slicer

Combined they provide the key analog processing functions for a number of video system applications. The operation of each of these blocks is described below.

Sync Separator

The sync separator contained in the EL4501C has been designed to be compatible with a wide range of video signal standards, operating with horizontal line rates from PAL/NTSC rates up to 150kHz. The sync separator

also includes a qualification scheme which rejects noise pulses and other video artifacts. The horizontal line rate timing is controlled with the use of a resistor, R_{FREQ} .

The following outputs are available:

- Composite sync
- Horizontal sync
- Vertical sync
- Burst gate
- Odd/Even field identification
- Loss of signal detected
- Sync amplitude detected

CONFIDENTIAL

EL4501C - Preliminary

Video Front End

General Disclaimer

Specifications contained in this data sheet are in effect as of the publication date shown. Elantec, Inc. reserves the right to make changes in the circuitry or specifications contained herein at any time without notice. Elantec, Inc. assumes no responsibility for the use of any circuits described herein and makes no representations that they are free from patent infringement.

élantec

HIGH PERFORMANCE ANALOG INTEGRATED CIRCUITS

Elantec Semiconductor, Inc.

675 Trade Zone Blvd.

Milpitas, CA 95035

Telephone: (408) 945-1323

(888) ELANTEC

Fax: (408) 945-9305

European Office: +44-118-977-6080

Japan Technical Center: +81-45-682-5820

WARNING - Life Support Policy

Elantec, Inc. products are not authorized for and should not be used within Life Support Systems without the specific written consent of Elantec, Inc. Life Support systems are equipment intended to support or sustain life and whose failure to perform when properly used in accordance with instructions provided can be reasonably expected to result in significant personal injury or death. Users contemplating application of Elantec, Inc. Products in Life Support Systems are requested to contact Elantec, Inc. factory headquarters to establish suitable terms & conditions for these applications. Elantec, Inc.'s warranty is limited to replacement of defective components and does not cover injury to persons or property or other consequential damages.