

## 450mA 9kV HIGH VOLTAGE DIODES

Finds use in applications such as Monitors, Static electricity dust collectors, Laser power supplies, ect..

### Features

- High speed switching
- High Current
- High surge resistivity for CRT discharge
- High reliability design
- High Voltage


### Applications

- X light Power supply
- Laser
- Voltage doubler circuit
- Microwave emission power

### Maximum Ratings and Characteristics

- Absolute Maximum Ratings

### Outline Drawings : mm



### Cathode Mark

| Type      | Mark |
|-----------|------|
| ESJC13-09 |      |

| Items                                | Symbols   | Condition                          | ESJC13-09   | Units             |
|--------------------------------------|-----------|------------------------------------|-------------|-------------------|
| Repetitive Peak Reverse Voltage      | $V_{RRM}$ |                                    | 9.0         | kV                |
| Average Output Current               | $I_o$     | $T_a=25^{\circ}C$ , Resistive Load | 450         | mA                |
| Surge Current                        | $I_{FSM}$ |                                    | 30          | A <sub>peak</sub> |
| Junction Temperature                 | $T_j$     |                                    | 125         | $^{\circ}C$       |
| Allowable Operation Case Temperature | $T_c$     |                                    | 125         | $^{\circ}C$       |
| Storage Temperature                  | $T_{stg}$ |                                    | -40 to +130 | $^{\circ}C$       |

### Electrical Characteristics ( $T_a=25^{\circ}C$ Unless otherwise specified)

| Items                         | Symbols  | Conditions                             | ESJC13-09 | Units   |
|-------------------------------|----------|--|-----------|---------|
| Maximum Forward Voltage Drop  | $V_F$    | at $25^{\circ}C$ , $I_F = I_{F(AV)}$   | 9.0       | V       |
| Maximum Reverse Current       | $I_{R1}$ | at $25^{\circ}C$ , $V_R = V_{RRM}$     | 5.0       | $\mu A$ |
|                               | $I_{R2}$ | at $100^{\circ}C$ , $V_R = V_{RRM}$    | 50        | $\mu A$ |
| Maximum Reverse Recovery Time | $T_{rr}$ | at $25^{\circ}C$                       | --        | nS      |
| Junction Capacitance          | $C_j$    | at $25^{\circ}C$ , $V_R=0V$ , $f=1MHz$ | --        | pF      |