


SBD Type : FSQ10A06

OUTLINE DRAWING

FEATURES

- *Similar to TO-220AC Case
- *Fully Molded Isolation
- *Low Forward Voltage Drop
- *Low Power Loss, High Efficiency
- *High Surge Capability
- *T_j=150 °C operation



Maximum Ratings

Approx Net Weight: 1.7g

Rating	Symbol	FSQ10A06		Unit
Repetitive Peak Reverse Voltage	V _{RRM}	60		V
Non-repetitive Peak Reverse Voltage	V _{RSM}	65		V
Average Rectified Output Current	I _o	10	T _C =111°C 50 Hz half Sine Wave Resistive Load	A
RMS Forward Current	I _{F(RMS)}	15.7		A
Surge Forward Current	I _{FSM}	150	50Hz Half Sine Wave ,1cycle Non-repetitive	A
Operating Junction Temperature Range	T _{jw}	-40 to +150		°C
Storage Temperature Range	T _{stg}	-40 to +150		°C
Mounting torque	F _{tor}	recommended torque = 0.5		N•m

Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	I _{RM}	T _j = 25°C, V _{RM} = V _{RRM}	-	-	10	mA
Peak Forward Voltage	V _{FM}	T _j = 25°C, I _{FM} = 10 A	-	-	0.67	V
Thermal Resistance	R _{th(j-c)}	Junction to Case	-	-	3	°C /W
	R _{th(c-f)}	Case to Fin	-	-	1.5	°C /W

FSQ10A06 OUTLINE DRAWING (Dimension in mm)

