



# 3.3V 1A Low Dropout Regulator with Disable

## Features

- Dropout voltage 0.5V @  $I_o = 1A$
- Output current in excess of 1A
- Output voltage accuracy  $\pm 2.5\%$
- Quiescent current, typically 5mA
- Internal short circuit current limit
- Internal over temperature protection
- TO220 4pin Full-Mold package
- ON/OFF control

## General Description


The G9133 positive 3.3V voltage regulator features the ability to source 1A of output current. The dropout voltage is 0.5V at 1A output current. The typical quiescent current is 5mA. Furthermore, the quiescent current is smaller when the regulator is in the dropout mode ( $V_{IN} < 3.3V$ ).

Familiar regulator features such as over temperature and over current protection circuits are provided to prevent it from being damaged by abnormal operating conditions. A  $V_{EN}$  pin is provided to disable the output when needed.

## Ordering Information

ORDER NUMBER	ORDER NUMBER (Pb free)	MARKING	TEMP. RANGE	PACKAGE	PIN OPTION			
					1	2	3	4
G9133TF1T	G9133TF1Tf	G9133	-40°C to +85°C	TO220F-4	$V_{IN}$	$V_o$	GND	$V_{EN}$
G9133TH1T	G9133TH1Tf	G9133	-40°C to +85°C	TO220F-4	$V_{IN}$	$V_o$	GND	$V_{EN}$

## Order Number Identification



### PACKAGE TYPE

TF : TO-220F-4 (short lead)

TH : TO-220F-4 (long lead)

1

1.:  $V_{IN}$ 

### PIN OPTION

2

 $V_o$ 

3

GND

### PACKING


T : Tube

4


 $V_{EN}$ 

## Package Type

### TO-220F-4



## Typical Application





<b>Absolute Maximum Ratings</b>	(Note 1)
Input Voltage	8V
V <sub>EN</sub> Voltage	8V
Power Dissipation Internally Limited	(Note 2)
Maximum Junction Temperature	150°C
Storage Temperature Range	-65°C ≤ T <sub>J</sub> ≤ +150°C
Reflow Temperature (soldering, 10sec)	260°C
Continuous Power Dissipation (T <sub>A</sub> = +25°C)	
TO220 No heatsink	1.5W
TO220 with infinite heatsink	15W

<b>Operating Conditions</b>	(Note 1)
Input Voltage	3.6V~7V
Temperature Range	-40°C ≤ T <sub>A</sub> ≤ 85°C
V <sub>EN</sub> Voltage	V <sub>IN</sub> +0.3V

## Electrical Characteristics

V<sub>IN</sub> = 5V, I<sub>O</sub> = 0.5A, C<sub>IN</sub> = 4.7μF, C<sub>OUT</sub> = 47μF, T<sub>A</sub> = T<sub>J</sub> = 25°C unless otherwise specified [Note 3]

PARAMETER	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
Output Voltage	V <sub>O</sub>	I <sub>O</sub> = 0.5A	3.217	3.3	3.383	V
Line Regulation		4V < V <sub>IN</sub> < 7V, I <sub>O</sub> = 10mA	---	0.5	2	%
Load Regulation		50mA ≤ I <sub>O</sub> ≤ 1A	---	0.5	2	%
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> = 5V, V <sub>EN</sub> = V <sub>IN</sub>	---	5	10	mA
		V <sub>IN</sub> = 5V, V <sub>EN</sub> = 0V	---	10	30	μA
Ripple Rejection		f <sub>i</sub> = 120Hz, 1V <sub>P-P</sub> , I <sub>O</sub> = 100mA	---	45	---	dB
Dropout Voltage	V <sub>D</sub>	I <sub>O</sub> = 1A	---	0.35	0.5	V
Short Circuit Current			---	3.8	---	A
Over Temperature			---	150	---	°C
Disable Voltage High	V <sub>ENH</sub>	Output Active	2.0	---	---	V
Disable Voltage Low	V <sub>ENL</sub>	Output Disabled	---	---	0.8	V
Disable Bias Current High	I <sub>ENH</sub>	V <sub>EN</sub> = 2.7V	---	---	20	μA
Disable Bias Current Low	I <sub>ENL</sub>	V <sub>EN</sub> = 0.4V	---	---	20	μA

**Note 1:** Absolute Maximum Ratings are limits beyond which damage to the device may occur. Operating Conditions are conditions under which the device functions but the specifications might not be guaranteed. For guaranteed specifications and test conditions see the Electrical Characteristics.

**Note2:** The maximum power dissipation is a function of the maximum junction temperature, T<sub>Jmax</sub>; total thermal resistance, θ<sub>JA</sub>, and ambient temperature T<sub>A</sub>. The maximum allowable power dissipation at any ambient temperature is T<sub>Jmax</sub>-T<sub>A</sub>/θ<sub>JA</sub>. If this dissipation is exceeded, the die temperature will rise above 150°C and IC will go into thermal shutdown. For the TO-220 package, θ<sub>JA</sub> is 60°C/W (No heat sink).

**Note3:** Low duty pulse techniques are used during test to maintain junction temperature as close to ambient as possible.

**Note4:** The type of output capacitor should be tantalum or aluminum.

## Definitions

### Dropout Voltage

The input/output Voltage differential at which the regulator output no longer maintains regulation against further reductions in input voltage. Measured when the output drops 2% below its nominal value, dropout voltage is affected by junction temperature, load current and minimum input supply requirements.

### Line Regulation

The change in output voltage for a change in input voltage. The measurement is made under conditions of low dissipation or by using pulse techniques such that average chip temperature is not significantly affected.

### Load Regulation

The change in output voltage for a change in load current at constant chip temperature. The measurement is made under conditions of low dissipation or by using pulse techniques such that average chip temperature is not significantly affected.


### Maximum Power Dissipation

The maximum total device dissipation for which the regulator will operate within specifications.

### Quiescent Bias Current

Current which is used to operate the regulator chip and is not delivered to the load.







Block Diagram





Typical Performance Characteristics


(VIN=5V, CIN=10μF, COUT =47μF, TA=25°C, unless otherwise noted.)






Typical Performance Characteristics (continued)


Dropout Voltage vs. Temperature




Load Regulation




Output Voltage vs. Temperature




Quiescent Current vs. Temperature





Output Voltage vs. Disable Voltage



Output Voltage vs. Input Voltage




Typical Performance Characteristics (continued)




**Heatsink Package Dimension**

TO-220F-4






Package Information



TO-220F-4 Package (short lead)

SYMBOL	DIMENSION IN MM			DIMENSION IN INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	4.42	4.57	4.72	0.174	0.180	0.186
A1	2.69	2.79	2.89	0.106	0.110	0.114
A2	1.68	1.78	1.88	0.066	0.070	0.074
D	10.00	10.10	10.20	0.394	0.398	0.402
E	6.85	6.95	7.05	0.269	0.273	0.278
E1	8.54	8.64	8.74	0.336	0.340	0.344
L	7.15	7.35	7.55	0.281	0.289	0.297
L1	16.56	16.66	16.76	0.652	0.656	0.660
L2	3.60	3.70	3.80	0.142	0.146	0.150
He	22.54	22.94	23.34	0.887	0.903	0.919
C	-----	0.48	-----	-----	0.019	-----
e	-----	2.54(TYP)	-----	-----	0.1(TYP)	-----
b	-----	0.635(TYP)	-----	-----	0.025(TYP)	-----
theta	4°	7°	11°	4°	7°	11°



TO-220F-4 Package (long lead)

SYMBOL	DIMENSION IN MM			DIMENSION IN INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	4.42	4.57	4.72	0.174	0.180	0.186
A1	2.69	2.79	2.89	0.106	0.110	0.114
A2	1.68	1.78	1.88	0.066	0.070	0.074
D	10.00	10.10	10.20	0.394	0.398	0.402
E	6.85	6.95	7.05	0.269	0.273	0.278
E1	8.54	8.64	8.74	0.336	0.340	0.344
L	13.15	13.35	13.55	0.518	0.526	0.533
L1	16.56	16.66	16.76	0.652	0.656	0.660
L2	3.60	3.70	3.80	0.142	0.146	0.150
He	28.44	28.94	29.44	1.119	1.139	1.159
C	-----	0.48	-----	-----	0.019	-----
e	-----	2.54(TYP)	-----	-----	0.1(TYP)	-----
b	-----	0.635(TYP)	-----	-----	0.025(TYP)	-----
$\theta$	4°	7°	11°	4°	7°	11°

Taping Specification

PACKAGE	Q'TY/BY TUBE
TO-220F-4	50 ea

GMT Inc. does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and GMT Inc. reserves the right at any time without notice to change said circuitry and specifications.