



Features

- ▶ Low cost
- ▶ Range of tolerances
- ▶ Excellent ageing characteristics
- ▶ Miniature size for high density applications
- ▶ Large stocks of popular specifications

Specifications

Parameters	Product	Option Code
	GWX-26	
Package:	2.0 x 6.0mm cylinder	
Frequency:	32.768kHz	
Calibration tolerance:	±20ppm ±15ppm ±10ppm	B A D
Operating temperature range:	-20 to +70°C -40 to +85°C	I
Storage temperature range:	-40 to +85°C	
Turnover temperature (T ₀):	+25°C ±5°C	
Frequency / temp coefficient:	-0.034ppm±0.006/°C ² typ	
Circuit condition:	12.5pF Other values	specify
Static capacitance (C ₀):	1.20pF typ	
Equivalent series resistance (max):	35kΩ 70kΩ (option I)	
Ageing (first year):	±3ppm max	
Drive level:	1.0μW max	

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + option codes (if any) + circuit condition (if non-standard)

eg: **GWX-26/B** ±20ppm, 12.5pF (standard)

GWX-26/A 8.0pF ±15ppm, 8.0pF

Option code X (eg GWX-26/X) denotes a custom specification.