

IPSL-M12 series

Low Range Industrial Pressure Sensor with M12 4Pin Connector



- Piezo-resistive sensor
- Stainless steel body & diaphragm
- Accuracy $\leq \pm 0.25\%$ FS BFSL
- 4-20mA or 0-5Vdc output.
- Pressure ranges from 50 mbar to 1000 mbar
- M12 4-pin connector

Options available on the IPSL pressure transmitter.

Pressure range

Output type

Mating cable and plug assemblies are available - see datasheet M12 Cable Set Series

The IPSL-M12 is suitable for use in a wide range of applications. The probe uses a piezo-resistive silicon sensor, giving excellent media compatibility within an oil filled 316L stainless steel housing

The electronics incorporate a microprocessor based amplifier, requiring no adjusting and giving stable electronics, especially in high vibration/shock applications.

Each device is temperature compensated, calibrated and supplied with a traceable serial number and calibration data.

Custom versions can be made for particular applications.

Suitable applications

HVAC	Mechanical engineering
Pneumatics	Environmental engineering
Rainwater harvesting	Automotive testing
Agricultural machinery	Tank gauging
Laboratory testing	IBC, IBC Tote or pallet tank

Performance

Accuracy (Non-Linearity & Hysteresis) $\leq \pm 0.25\%$ / FS (BFSL) for gauge, $\leq \pm 0.5\%$ for Absolute

Setting Errors (offsets)	2-wire	Zero & Full Scale, $\leq \pm 0.5\%$ / FS
	3-wire	Zero & Full Scale, $\leq \pm 0.5\%$ / FS
Permissible Load	2-wire	$R_{max} = [(Supply-9min)/0.02]\Omega$
	3-wire	$R_{min} = 10k\Omega$
Influence Effects	Supply	$\leq 0.005\%$ FS / 1V
	Load	0.05% FSO / k Ω

Material Specifications

Housing	316L Stainless Steel
"O" ring seals	Viton
Diaphragm	316L Stainless Steel
Media wetted parts	Housing & connection, "O" ring seal, diaphragm

Miscellaneous

Current consumption	2-wire Limits at 28mA 3-wire Typical 6mA
Weight	Approx 100g
Installation position	Any, small zero shift when tilted through 90°
Operational Life	$> 100 \times 10^6$ cycles
Insulation resistance	$> 50M\Omega$ at 50Vdc
Environmental protection	IP67 (when used with a similarly rated connector)

Electrical Protection

Supply reverse polarity	No damage/no function
Electromagnetic compatibility	CE Compliant

Mechanical Stability

Shock	100g / 11s
Vibration	10g RMS (20 - 2000Hz)

Temperatures & Thermal Effects

Media Temperature	-40°C to +125°C
Ambient Temperature	-20°C to +80°C
Storage temperature	-40°C to +125°C
Compensated temperature range	+20°C to +80°C
Thermal Zero Shift (TZS)	$\leq \pm 0.04\%$ / FS/°C
Thermal Span Shift	$\leq -0.015\%$ /°C

Cynergy3 Components Ltd.
7 Cobham Road
Ferndown Industrial Estate
Wimborne, Dorset BH21 7PE
Telephone +44 (0) 1202 897969
Email: sales@cynergy3.com

IPSL-M12 2018

ISO9001 CERTIFIED



www.cynergy3.com

IPSL-M12 series

Low Range Industrial Pressure Sensor with M12 4Pin Connector

Pressure Ranges and Passive mV/V Outputs

Nominal Pressure, Gauge, mbar	50	100	250	500	750	1000
Nominal Pressure, Absolute mbar				500	750	1000
Permissible Overpressure mbar	2 bar	2 bar	2 bar	5 bar	5 bar	5 bar

Output Signals and Supply Voltages DIN 43650

Wire system	Output	Supply Volts	Connection	Pin No.
2-wire	4-20mA	9-32Vdc	+ve Supply -ve Supply Ground	Pin 1 Pin 2 Earth pin
3-wire	0 - 5Vdc	9-32 Vdc	+ve Supply -ve Supply +ve Output Ground	Pin 1 Pin 2 Pin 3 Pin 4 Earth

Part No.	Pressure Range	Output
IPSL-G0050-5M12	0-50mbarG	4-20mA
IPSL-G0100-5M12	0-100mbarG	4-20mA
IPSL-G0250-5M12	0-250mbarG	4-20mA
IPSL-G0500-5M12	0-500mbarG	4-20mA
IPSL-G0750-5M12	0-750mbarG	4-20mA
IPSL-G1000-5M12	0-1000mbarG	4-20mA
IPSL-G0050-6M12	0-50mbarG	0-5V 3-wire
IPSL-G0100-6M12	0-100mbarG	0-5V 3-wire
IPSL-G0250-6M12	0-250mbarG	0-5V 3-wire
IPSL-G0500-6M12	0-500mbarG	0-5V 3-wire
IPSL-G0750-6M12	0-750mbarG	0-5V 3-wire
IPSL-G1000-6M12	0-1000mbarG	0-5V 3-wire

