



LEOPARD IMAGING INC

Rev. 1.0

LI-USB30-OV2311

Data Sheet

Key Features

- USB 3.0 Super Speed support
- 10-bit RAW data output without compression
- UVC compliance
- Monochrome sensor
- Global shutter
- Resolution: 1600 x 1300
- Frame rate: 30 fps
- Support register access function
- Provide customization services
- USB +5VDC powered device
- Compact Size: 26mmx26mm
- 2 Boards are stacked
- Part#: **LI-USB30-OV2311**
- Support multiple module options
- Default OV2311 module Part#: **LI-OV2311-MIPI-125H**



Lens Specification


- Focusing Range: 50cm to Infinity
- Focal length: 2.2 mm
- F/#: 2.5
- FOV (H): 125 °
- TV Distortion < -87.6%

Applications

- Machine Vision
- Scientific Camera

SDK Supported

- Camera Tool Source Code in C#
- Capture & Display
- RAW to Grayscale Conversion
- Save file as BMP & RAW format
- Access registers



RAW data streaming



Camera Tool view mode



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com

Specification

General Behavior	
Video Resolution @ Frame rate	1600 x 1300 @ 30 fps
Dynamic range	10 bit
Interface (Optical)	
IR cut filter (on lens)	No
Sensor specification	OmniVision CMOS 2MP image sensor OV2311
Shutter	Global shutter
Format	1/2.9"
Resolution	H:1600, V:1300
Pixel size	H: 3 um, V: 3 um
Interface (Electrical)	
Interface	USB 3.0
Supply voltage	USB 3.0 +5 VDC power source
Current consumption	Approx. 225 mA at 5 VDC
Interface (Mechanical)	
Dimensions	L: 26 mm, W: 26 mm, H: 20 mm
Mass	20 g
Adjustment (Manual)	
Shutter	Support
Gain	Support
Register Access	Support
Adjustment (Auto)	
Shutter	TBD
Gain	TBD
Environmental	
Max. temperature (operation)	0 °C ~ 50 °C (32 °F~ 122 °F)
Max. temperature (storage)	-20 °C ~ 80 °C (-4 °F~176 °F)
Max. humidity (operation)	20 % ~ 80 %, relative, non-condensing
Max. humidity (storage)	20 % ~ 80 %, relative, non-condensing



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com