

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A

Preliminary Datasheet


Features

- ◆ **2 Watt Saturated Output Power Level**
- ◆ **Variable Drain Voltage (6-10V) Operation**
- ◆ **MSAG™ Process**
- ◆ **5x5 mm 20 Lead PQFN Package**

Description

The MAAP-000067-PKG003 is a 3-stage 2 W power amplifier with on-chip bias networks in a 20 lead MLP package, allowing easy assembly. This product is fully matched to 50 ohms on both the input and output. It can be used as a power amplifier stage or as a driver stage in high power applications.

Each device is 100% RF tested to ensure performance compliance. The part is fabricated using M/A-COM's GaAs Multifunction Self-Aligned Gate (MSAG™) Process.



Primary Applications:

- ◆ **Point-to-Point Radio**
- ◆ **SatCom**

Also Available in:

		SAMPLES		
Description	Die	Sample Board (Die)	Sample Board (Package)	Mechanical Sample (Die)
Part Number	MAAPGM0067-DIE	MAAP-000067-SMB004	MAAP-000067-SMB003	MAAP-000067-MCH000

Electrical Characteristics: $T_C = 35^\circ C^1$, $Z_0 = 50\Omega$, $V_{DD} = 8V$, $I_{DQ} = 640mA^2$, $P_{in} = 12dBm$, $R_G=150\Omega$

Parameter	Symbol	Typical	Units
Bandwidth	f	5.7-8.5	GHz
Output Power	P_{OUT}	33	dBm
1-dB Compression Point	P_{1dB}	33	dBm
Small Signal Gain	G	26	dB
Power Added Efficiency	PAE	30	%
Input VSWR	VSWR	1.7:1	
Output VSWR	VSWR	2.5:1	
Gate Supply Current	I_{GG}	7	mA
Drain Supply Current, under RF Drive	I_{DD}	900	mA
Output Third Order Intercept	TOI	41	dBm
Output Third Order Intermod, Single Carrier Level = 23 dBm	IM3	35	dBc

1. T_C = Case Temperature
2. Adjust V_{GG} between -2.6 and $-1.2V$ to achieve specified I_{DQ} .

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. M/A-COM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does M/A-COM assume any liability whatsoever arising out of the use or application of any product(s) or information.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298

Visit www.macom.com for additional data sheets and product information.

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A
Preliminary Datasheet

Maximum Ratings³

Parameter	Symbol	Absolute Maximum	Units
Input Power	P_{IN}	17	dBm
Drain Supply Voltage	V_{DD}	+12.0	V
Gate Supply Voltage	V_{GG}	-3.0	V
Quiescent Drain Current (No RF)	I_{DQ}	1.02	A
Quiescent DC Power Dissipated (No RF)	P_{DISS}	10.2	W
Junction Temperature	T_J	170	°C
Storage Temperature	T_{STG}	-55 to +150	°C

3. Operation beyond these limits may result in permanent damage to the part.

Recommended Operating Conditions⁴

Characteristic	Symbol	Min	Typ	Max	Unit
Drain Supply Voltage	V_{DD}	6.0	8.0	10.0	V
Gate Supply Voltage	V_{GG}	-2.6	-2.0	-1.2	V
Input Power	P_{IN}		12.0	15.0	dBm
Thermal Resistance	Θ_{JC}		15.6		°C/W
Case Temperature	T_C			Note 5	°C

4. Operation outside of these ranges may reduce product reliability.


5. Case Temperature = $170^{\circ}\text{C} - \Theta_{JC} * V_{DD} * I_{DQ}$



Operating Instructions

This device is static sensitive. Please handle with care. To operate the device, follow these steps.

1. Apply $V_{GG} = -2.7\text{V}$, $V_{DD} = 0\text{V}$.
2. Ramp V_{DD} to desired voltage, typically 8.0 V.
3. Adjust V_{GG} to set I_{DQ} , (approximately @ -2.0V).
4. Set RF input.
5. Power down sequence in reverse. Turn V_{GG} off last.



**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A

Preliminary Datasheet




Figure 1. 1dB Compression Point vs. Frequency and Drain Voltage at IDQ = 640mA




Figure 2. Small Signal Gain and Input & Output VSWR vs. Frequency and Drain Voltage at IDQ = 640 mA




Figure 3. Saturated Output Power vs. Frequency and Drain Voltage at IDQ = 640mA




Figure 4. Saturated Power Added Efficiency vs. Frequency and Drain Voltage at IDQ = 640mA




Figure 5. Saturated Output Power vs Frequency and Case Temperature at Vd = 8V and IDQ = 640mA




Figure 6. Small Signal Gain & Saturated Output Power, Power Added Efficiency, and Drain Current vs Case Temperature at 7GHz, VD = 8V and IDQ = 640mA

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A

Preliminary Datasheet




Figure 7. Output Power vs. Input Power and Frequency at VD = 6V and IDQ = 640mA




Figure 8. Gain vs. Output Power and Frequency at VD = 6V and IDQ = 640mA




Figure 9. Output Power vs. Input Power and Frequency at VD = 8V and IDQ = 640mA




Figure 10. Gain vs. Output Power and Frequency at VD = 8V and IDQ = 640mA




Figure 11. Output Power vs. Input Power and Frequency at VD = 10V and IDQ = 640mA




Figure 12. Gain vs. Output Power and Frequency at VD = 10V and IDQ = 640mA

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A

Preliminary Datasheet

VD = 6V




Figure 13. Power Added Efficiency vs. Input Power and Frequency at VD = 6V and IDQ = 640mA




Figure 14. Drain Current vs. Input Power and Frequency at VD = 6V and IDQ = 640mA

VD = 8V




Figure 15. Power Added Efficiency vs. Input Power and Frequency at VD = 8V and IDQ = 640mA




Figure 16. Drain Current vs. Input Power and Frequency at VD = 8V and IDQ = 640mA

VD = 10V




Figure 17. Power Added Efficiency vs. Input Power and Frequency at VD = 10V and IDQ = 640mA




Figure 18. Drain Current vs. Input Power and Frequency at VD = 10V and IDQ = 640mA

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A

Preliminary Datasheet

VD = 6V




Figure 19. Third Order Intercept vs. Output Power and Frequency at VD = 6V and IDQ = 640mA




Figure 20. Third Order Intermod vs. Output Power and Frequency at VD = 6V and IDQ = 640mA

VD = 8V




Figure 21. Third Order Intercept vs. Output Power and Frequency at VD = 8V and IDQ = 640mA




Figure 22. Third Order Intermod vs. Output Power and Frequency at VD = 8V and IDQ = 640mA

VD = 10V




Figure 23. Third Order Intercept vs. Output Power and Frequency at VD = 10V and IDQ = 640mA




Figure 24. Third Order Intermod vs. Output Power and Frequency at VD = 10V and IDQ = 640mA

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A

Preliminary Datasheet




Figure 25. Third Order Intercept vs. Temperature and Frequency at Single Carrier Output Power Level = 23 dBm, VD = 8V and IDQ = 640mA




Figure 26. Third Order Intermod vs. Temperature and Frequency at Single Carrier Output Power Level = 23 dBm, VD = 8V and IDQ = 640mA

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A
Preliminary Datasheet




Figure 27. 5x5 mm 20-Lead MLP.




Figure 28. Recommended Bias Configuration.

Note: The exposed pad centered on the package bottom must be connected to RF and dc ground for proper electrical and thermal operation.

Refer to M/A-COM Application Note **Surface Mounting Instructions for PQFN Packages #S2083*** for assembly guidelines.

Additional Precaution: All parts must receive a bake-out of 125°C for 24 hours prior to any solder reflow operation.

*Application Notes can be found by going to the Site Search Page of M/A-COM's web page (<http://www.macom.com/Application%20Notes/index.htm>) and searching for the required Application Note.

**Amplifier, Power, 2W
5.7-8.5 GHz**

MAAP-000067-PKG003

Rev A
Preliminary Datasheet




Figure 29. Demonstration Board PN MAAP-000067-SMB003 (available upon request).