



3.5 mm Plugs

— NEW —

3.5 mm stereo plugs feature heavy duty cable clamp for superior strain relief, knurled surface on handle provides a sure grip, oversized solder terminal for ease of assembly.

Stock No.	Mfr.'s Type	Fig.	No. of Contacts	Handle Plugs	EACH		
					1-9	10-24	25-99
514-8000	NYS231	1	3	Nickel/Nickel	.75	.65	.55
514-8001	NYS231AU	1	3	Nickel/Gold	1.20	1.00	.90
514-8002	NYS231B	1	3	Black/Gold	1.20	1.00	.90
514-8003	NYS231-BAG	1	3	Black/Gold	.90	.85	.70

PowerCon® — 3 Pole Equipment (AC) Connector

Stock No.	Mfr.'s Type	Fig.	Description	EACH		
				1-9	10-24	25-99
514-8666	NAC3FCA*	2	Cable connector, quick lock with securing lever, blue	5.77	5.14	4.69
514-8668	NAC3FCB†	3	Cable connector, quick lock with securing lever, grey with blue bushing	5.77	5.14	4.69
514-8670	NAC3MPA*	4	Chassis connector, air tight, blue	2.89	2.58	2.35
514-8672	NAC3MPB†	4	Chassis connector, air tight, grey	2.89	2.58	2.35

*Power inlet. †Power outlet.

ProFi® — Professional "RCA" Connector

- ▶ All Metal Design, Machined Brass, Black Coated Shell
- ▶ Easy Assembly and Soldering (Large Soldering Area, Rapid-Flow Plating)
- ▶ High-Grade Plastic Insulator with High Creep Resistance
- ▶ Spring Loaded Ground Contact: Retractable Element with Separate Wedge Contacts Which Keep the Shell in the Front Position When Engaged

Contacts for line, neutral, and pre-mating safety grounds and are designed to prevent damage from arcing when disconnected while under load. Rated at 20 A/250 VAC. Different keying avoids intermating errors. POWERCON IS NOT DESIGNED TO BE A "MAINS" CONNECTOR.

Stock No.	Mfr.'s Type	Fig.	Description	EACH		
				1-9	10-24	25-99
514-8674	NF2C-B/2	5	Two plugs with red/black colored sleeves and two strain relief chucks for small or large cable diameters	16.55	15.18	13.87

1/4" Professional Phone Plugs

Nickel plated brass plugs. Accept 0.10"-0.28" diameter cable. Standard or right angle; right angle also available in "slim" version with solderless ground contact.

Stock No.	Mfr.'s Type	Fig.	No. of Contacts	Shell	EACH		
					1-9	10-24	25-99
514-1074	NP2RC	—	2	Nickel	5.51	4.37	4.08
514-1078	NP2RCS*	6	2	Nickel	3.27	2.89	2.61
514-1101	NP3RC	—	3	Nickel	6.39	6.23	4.92
514-8664	NP3RCS*	6	3	Nickel	5.42	4.83	4.41
514-1072	NP2C	7	2	Nickel	3.19	2.43	2.27
514-1073	NP3C	7	3	Nickel	4.47	3.50	3.29
514-1075	NP2C-BAG	7	2	Black	3.29	2.78	2.56
514-1076	NP3C-BAG	7	3	Black	4.72	3.76	3.45

*New slim line right angle plug.

1/4" Economical Phone Plugs

▶ AWG: 14 AWG — 224L; 18 AWG — 201, 202, 203, 204, 224, 228
▶ 500 Vrms

Stock No.	Mfr.'s Type	Fig.	Description	EACH		
				1-9	10-24	25-99
514-8614	NYS 201	8	2 pole short barrel	1.23	1.07	.97
514-8616	NYS 202	8	3 pole short barrel	1.73	1.49	1.36
514-8618	NYS 224	9	2 pole long barrel shielded handle	1.27	1.10	1.00
514-8620	NYS 224L	9	2 pole long barrel shielded large handle	1.34	1.16	1.05
514-8622	NYS 228	9	3 pole long barrel shielded handle	2.31	2.04	1.85
514-8624	NYS 203	10	2 pole plastic shell with plastic strain relief	1.17	1.01	.92
514-8626	NYS 204	10	3 pole plastic shell with plastic strain relief	1.27	1.10	1.00
514-8700	NYS 225	11	2 pole large barrel shielded handle*	2.44	2.15	1.96
514-8702	NYS 225B	11	2 pole large barrel shielded handle, black*	2.44	2.15	1.96

*Cable dia. range up to 0.355".

Economical "RCA" Phono Connectors

▶ 500 Vrms

Stock No.	Mfr.'s Type	Fig.	Description	EACH		
				1-9	10-24	25-99
514-8628	NYS 352	12	2 pole long barrel large shielded handle, cable dia. range up to 0.25	.89	.77	.70
514-8704	NYS 352G	12	2 pole long barrel shielded handle, cable dia. range up to 0.25, gold contact	1.31	1.14	1.04
514-8630	NYS 354	13	2 pole right angle PCB phono jack	.54	.46	.43
514-8632	NYS 355	14	2 pole phono to phono female adapter	2.58	2.24	2.04

1/4" Economical Phone Jacks — Solder and P.C.

▶ 500 Vrms

Stock No.	Mfr.'s Type	Fig.	Description	EACH		
				1-9	10-24	25-99
514-8634	NYS 220	15	2 pole solder lugs with strain relief clamp	2.06	1.78	1.61
514-8636	NYS 221	16	3 pole solder lugs with strain relief clamp	2.14	1.86	1.68
514-8637	NYS 212*	—	3 pole solder tab	.65	.57	.51
514-8638	NYS 215*	17	3 pole right angle washer and chrome nut, 0.322"	.80	.70	.63
514-8640	NYS 216*	17	3 pole right angle nut and washer, 0.322"	.65	.57	.51
514-8642	NYS 218*	18	3 pole right angle nut and washer, 0.492"	.63	.55	.49
514-8644	NYS 219*	19	3 pole right angle nut and washer, 0.590"	.65	.57	.51
514-8646	NYS 229	20	2 pole solder lug insulated washer, 0.0375" mounting hole	.93	.81	.73
514-8650	NYS 230	21	3 pole solder lug insulated washer, 0.0375" mounting hole	1.04	.90	.82

*Mono version is available as a special order by adding /2 to the part no.

Circular DIN Connectors — Cable and Panel

▶ 500 Vrms

Stock No.	Mfr.'s Type	Fig.	Description	EACH		
				1-9	10-24	25-99
514-8652	NYS 321	22	3 pin 180° male	1.21	1.05	.95
514-8654	NYS 322	22	5 pin 180° male	1.25	1.09	.99
514-8656	NYS 323	22	7 pin 270° male	3.12	2.32	2.15
514-8658	NYS 324	23	3 contact 180° female	.50	.43	.39
514-8660	NYS 325	23	5 contact 180° female	.56	.48	.44
514-8662	NYS 326	23	7 contact 270° female	.63	.55	.49