miRata

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NCP18WM154J03RB from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=NCP18WM154J03RB

NCP18WM154J03RB

In Production Recommended RoHS REACH

Appearance & Shape





Features

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible

5. Same B-Constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

Easy to use smaller size in the circuits

- 6. Lead is not contained in the product.
- 7. NCP series are recognized by UL/cUL (UL1434, File No.E137188).

Applications

Limited Usage	Consumer Grade
Other Usage	 Temperature compensation for transistor, IC and crystal oscillator in mobile communications Temperature sensor for rechargeable batteries Temperature compensation of LCD Temperature compensation in general use of electric circuits



Packaging	Specifications	Minimum Order Quantity
RB	180mm Paper Tape	4000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NCP18WM154J03RB from the official website of Murata Manufacturing

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=NCP18WM154J03RB

NCP18WM154J03RB

Specifications

Resistance (25°C)	150κΩ
Resistance Value Tolerance (at 25°C)	±5%
B-Constant (25/50°C)	4500K
B-Constant (25/50°C) Tolerance	±3%
B-Constant(25/80°C)(Reference Value)	4571K
B-Constant(25/85°C)(Reference Value)	4582K
B-Constant(25/100°C)(Reference Value)	4614K
Permissive Operating Current (25°C)	0.08mA
Rated Electric Power (25°C)	100.0mW
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40℃ to 125℃
Size Code (in mm)	1.6x0.8mm
Size Code (in inch)	0.6x0.3inch
Shape	SMD
Mass	0.0047g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet




NCP18WM154J03RB

Note: This datasheet may be out of date.

Please download the latest datasheet of NCP18WM154J03RB from the official website of Murata Manufacturing Co., Ltd.

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=NCP18WIM154J03RB





Resistance-Temperature Characteristics

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3