


NTCG064EF104HTBX



Applications	Commercial Grade
Features	125°C UL Certificate
Series	NTCG
Status	Production
Brand	TDK



Size	
Length(L)	0.60mm ±0.03mm
Width(W)	0.30mm ±0.03mm
Thickness(T)	0.30mm ±0.03mm
Terminal Width(B)	0.10mm Min.
Recommended Land Pattern (PA)	0.30mm ±0.05mm
Recommended Land Pattern (PB)	0.25mm ±0.05mm
Recommended Land Pattern (PC)	0.30mm ±0.05mm

Electrical Characteristics	
Resistance [at 25°C]	100kΩ
Resistance Tolerance	±3%
B value (Typ.) [25/50°C]	4250K
B value (Typ.) [25/85°C]	4308K
B value (Typ.) [25/100°C]	4327K
B value Tolerance	±1%
Max. Electric Power [at 25°C]	100mW
Permissible Operating Current [at 25°C]	100μA
Thermal Dissipation Constant [at 25°C]	1mW/°C 1mW/K


Other	
Max. Operating Temperature	125°C
Soldering Method	Reflow
UL File No.	E250289
AEC-Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	15000pcs
Weight	0.0003g

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

NTCG064EF104HTBX



Associated Images



! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.