


NTCG204AH683JT1



<b>Applications</b>	Commercial Grade
<b>Features</b>	125°C UL Certificate
<b>Series</b>	NTCG
<b>Status</b>	Production
<b>Brand</b>	TDK



Size	
Length(L)	2.00mm ±0.20mm
Width(W)	1.25mm ±0.20mm
Thickness(T)	0.70mm ±0.20mm
Terminal Width(B)	0.20mm Min.
Recommended Land Pattern (PA)	1.05mm ±0.15mm
Recommended Land Pattern (PB)	0.80mm ±0.10mm
Recommended Land Pattern (PC)	1.05mm ±0.15mm

Electrical Characteristics	
Resistance [at 25°C]	68kΩ
Resistance Tolerance	±5%
B value (Typ.) [25/50°C]	3931K
B value (Typ.) [25/85°C]	4000K
B value (Typ.) [25/100°C]	4023K
B value Tolerance	±3%
Max. Electric Power [at 25°C]	200mW
Permissive Operating Current [at 25°C]	170μA
Thermal Dissipation Constant [at 25°C]	2mW/°C   2mW/K


Other	
Max. Operating Temperature	125°C
Soldering Method	Reflow
UL File No.	E250289
AEC-Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	2000pcs
Weight	0.0072g

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

NTCG204AH683JT1



## Associated Images



! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.