

NTE1213 Integrated Circuit TV Video IF Amp

Functions:

- 1st Video IF Amplifier
- 2nd Video IF Amplifier
- Forward AGC Amplifier
- Reverse AGC Amplifier

Absolute Maximum Ratings:

Supply Voltage, V_{CC} 15V
 Power Dissipation ($T_A = +85^\circ\text{C}$), P_D 460mW
 Operating Temperature Range, T_{opg} -20° to $+85^\circ\text{C}$
 Storage Temperature Range, T_{stg} -55° to $+125^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Total Supply Current	I_{TS}	$V_{CC} = 12V, V_8 = 0V, R_L = 75k\Omega, \text{Pin9: Open}$	14.3	–	33.4	mA
Maximum Operating Current	I_{Tmax}	$V_{CC} = 12V, V_8 = 7V, R_L = 4.7k\Omega, \text{Pin9: Open}$	16.4	–	38.4	mA
Voltage Gain	G_{Vmax}	$V_{CC} = 12V, V_8 = 0V, V_9 = 8V, f = 57\text{MHz}$	51.0	–	–	dB
	G_{Vmin}	$V_{CC} = 12V, V_8 = 6V, V_9 = 8V, f = 57\text{MHz}$	–	–	4.0	dB
Forward AGC Voltage	V_{Fmin}	$V_{CC} = 12V, V_8 = 0V, R_L = 75k\Omega, \text{Pin9: Open}$	3.62	–	4.18	V
	V_{Fmax}	$V_{CC} = 12V, V_8 = 8V, R_L = 4.7k\Omega, V_9 = 11V$	6.5	–	–	V
Reverse AGC Voltage	V_{Rmin}	$V_{CC} = 12V, V_8 = 7V, V_9 = 11V, R_L = \infty$	–	–	1.0	V
	V_{Rmax}	$V_{CC} = 12V, V_8 = 0V, R_L = \infty, \text{Pin9: Open}$	10.0	–	–	V
IF AGC Voltage	$V_{IFAGCmin}$		–	–	2	V
	$V_{IFAGCmax}$		8	–	–	V

Pin Connection Diagram

