

# PLT-6S



## Parking Lifts

SKU# 5175220

6,000-lb. Capacity / Platform Parking Lift

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

## Your Future Favorite Lift

BendPak's PLT-6S [parking lift](#) was designed for both commercial and residential use and is the perfect car parking solution when ceiling clearances are limited and vehicle heights are restricted. Each PLT-6S parking lift features dual hydraulic lifting cylinders a high-strength safety lock system.

## Features

- 6,000-lb. lifting capacity
- Accommodates cars and small SUVs
- Heavy steel locks automatically engage at full-rise
- Manually operated lock release
- Dual hydraulic lifting cylinders
- Cantilevered design with lateral torsion bar
- No chains or cables
- Individual, or single multi-unit power unit configurations
- For commercial or residential applications
- Manually operated lock release
- Hydraulic safety valves (velocity fuses)
- Available in 110V or commercial 220V power options



## Specifications

**Lifting Capacity** 7,000 lbs. (3,175 kg)

**Overall Width** 98.3" (2,497 mm)

**Overall Length** 153.5" (3,899 mm)

**Overall Height** 74" (1,880 mm)

**Platform Width** 79.1" (2,010 mm)

**Platform Length** 134.9" (3,427 mm)

**Platform Rise** 50.6" (1,286 mm)

**Ramp Rise** 62.9" (1,599 mm)

**Leg Length** 98.8" (2,509 mm)

**Lifting Time** 55 sec

**Standard Motor** 220 VAC / 60 Hz / 1Ph

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult [www.autolift.org](http://www.autolift.org) for complete listings or contact BendPak via [contact@bendpak.com](mailto:contact@bendpak.com).

Multi-station power unit and special voltages available upon request.