



DESCRIPTION

PT6351 is a Vacuum Fluorescent Display Driver IC utilizing CMOS Technology. 28 High Voltage Ports, 17 All Purpose I/O Ports, 9 LED ports, Auto Scan Operation, 4-line Serial Signal (with chip selector), 8 DGT x 8 SG to 16 DGT x 12 SG are all incorporated into a single chip to build a highly reliable peripheral device for a single chip microcomputer. It is housed in 44-pin LQFP Package and is functionally compatible with MN12510F.

FEATURES

- CMOS Technology
- 28 High Voltage Output Ports: 8 to 16 Digit Ports
8 to 16 Segment Ports
- 17 All-Purpose I/O Ports
- 9 LED Drive Capable Ports
- Display Modes: 8 DGT x 8 SG to 16 DGT x 12 SG or up to 12 DGT x 16 SG
- 32 Bytes Display Data
- Key Scan Input: 5x12 (max.)
- Display ON/OFF Control
- Auto Scan Operation
- Power ON Reset Circuit
- Supply Voltage: Digital Section: $V_{DD} = 4.5$ to 5.5 V
High Voltage: $V_{pp} = V_{DD} - 35$ V
- Available in 44-pin, LQFP Package
- Functionally Compatible with MN12510F

APPLICATION

- Peripheral Device for Micro-Computer



PIN CONFIGURATION



