



PINGWEI ENTERPRISE

## R1200 THRU R3000

### 0.5&0.2AMPS.HIGH VOLTAGE SILICON RECTIFIER


#### FEATURE

- . High current capability
- . Low forward voltage drop
- . Low power loss, high efficiency
- . High surge capability
- . High voltage
- . High temperature soldering guaranteed  
260°C /10sec/ 0.375" lead length at 5 lbs tension

#### MECHANICAL DATA

- . Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C
- . Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
- . Polarity: color band denotes cathode
- . Mounting position: any

#### DO-41



Dimensions in inches and (millimeters)

#### MAXIMUM RATINGS AND ELECTRONICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

Type Number	SYMBOL	R1200	R1500	R1800	R2000	R2500	R3000	units
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	1200	1500	1800	2000	2500	3000	V
Maximum RMS Voltage	$V_{RMS}$	840	1050	1260	1400	1750	2100	V
Maximum DC Blocking Voltage	$V_{DC}$	1200	1500	1800	2000	2500	3000	V
Maximum Average Forward rectified Current at $T_A=50^\circ\text{C}$	$I_{F(AV)}$	0.5			0.2			A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rate load (JEDEC method)	$I_{FSM}$	30						A
Maximum Forward Voltage Drop per element at 0.5/0.2A DC	$V_F$	2.0			3.0		4.0	V
Maximum DC Reverse Current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	$I_R$	5.0						$\mu\text{A}$
Maximum Full Load Reverse Current Average, Full Cycle .375"(9.5mm) lead length at $T_L=55^\circ\text{C}$		30						
Typical Junction Capacitance (Note)	$C_J$	30						pF
Storage Temperature	$T_{STG}$	-55 to +150						$^\circ\text{C}$
Operation Junction Temperature	$T_J$	-55 to +125						$^\circ\text{C}$