




# R1200F THRU R2000F


## HIGH VOLTAGE FAST RECOVERY RECTIFIER

Reverse Voltage - 1200 to 2000 Volts Forward Current -0.5/0.2 Ampere

**DO-41**



**DO-15**



Dimensions in inches and (millimeters)

### FEATURES

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ Construction utilizes void-free molded plastic technique
- ◆ Low reverse leakage
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed:  
250°C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

### MECHANICAL DATA

**Case:** JEDEC DO-41/DO-15 molded plastic body  
**Terminals:** Plated axial leads, solderable per MIL-STD-750, Method 2026  
**Polarity:** Color band denotes cathode end  
**Mounting Position:** Any  
**Weight:** 0.012 ounce, 0.33 grams (DO-41)  
 0.014 ounce, 0.40 grams (DO-15)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
 Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

MDD Catalog Number	SYMBOLS	R1200F	R1500F	R1800F	R2000F	UNITS
Maximum repetitive peak reverse voltage	$V_{RRM}$	1200	1500	1800	2000	VOLTS
Maximum RMS voltage	$V_{RMS}$	840	1050	1260	1400	VOLTS
Maximum DC blocking voltage	$V_{DC}$	1200	1500	1800	2000	VOLTS
Maximum average forward rectified current 0.375" (9.5mm) lead length (see fig.1)	$I_{(AV)}$	0.5			0.2	Amp
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	30.0				Amps
Maximum instantaneous forward voltage at 0.5/0.2 A	$V_F$	2.5		4.0		Volts
Maximum DC reverse current $T_A=25^\circ C$ at rated DC blocking voltage $T_A=100^\circ C$	$I_R$	5.0 50.0				$\mu A$
Maximum reverse recovery time (NOTE 1)	$t_{rr}$	500				ns
Typical junction capacitance (NOTE 2)	$C_J$	15.0				pF
Typical thermal resistance (NOTE 3)	$R_{\theta JA}$	50.0				$^\circ C/W$
Operating junction and storage temperature range	$T_J, T_{STG}$	-65 to +150				$^\circ C$

- Note:**
1. Reverse recovery condition  $I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$
  2. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
  3. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted




www.microdiode.com

# RATINGS AND CHARACTERISTIC CURVES R1200F THRU R2000F


AVERAGE FORWARD RECTIFIED CURRENT,  
AMPERES

FIG. 1- FORWARD CURRENT DERATING CURVE




PEAK FORWARD SURGE CURRENT,  
AMPERES

FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



INSTANTANEOUS FORWARD CURRENT, AMPERES


FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



INSTANTANEOUS FORWARD VOLTAGE,  
VOLTS


INSTANTANEOUS REVERSE CURRENT,  
MICROAMPERES

FIG. 4-TYPICAL REVERSE CHARACTERISTICS




JUNCTION CAPACITANCE, pF

FIG. 5-TYPICAL JUNCTION CAPACITANCE



TRANSIENT THERMAL IMPEDANCE,  
°C/W

FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE



The cruve graph is for reference only, can't be the basis for judgment(曲线图仅供参考)!



www.microworld.com