



# DATA SHEET

## SB820CT~SB8100CT

### SCHOTTKY BARRIER RECTIFIERS

VOLTAGE 20 to 100 Volts CURRENT - 8 Ampere

#### FEATURES


- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound.
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency.
- Low forward voltage, high current capability
- High surge capacity.
- For use in low voltage, high frequency inverters free wheeling, and polarity protection applications.

#### MECHANICAL DATA

Case: TO-220AB full molded plastic package  
 Terminals: Lead solderable per MIL-STD-202, Method 208  
 Polarity: As marked.  
 Mounting Position: Any  
 Weight: 0.08 ounces, 2.24grams.

#### TO-220AB

Unit: inch ( mm )



#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
 Single phase, half wave, 60 Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%


|  | SB820CT     | SB830CT | SB840CT | SB850CT | SB860CT | SB880CT | SB8100CT | UNITS |
|--|-------------|---------|---------|---------|---------|---------|----------|-------|
| Maximum Recurrent Peak Reverse Voltage   | 20          | 30      | 40      | 50      | 60      | 80      | 100      | V     |
| Maximum RMS Voltage  | 14          | 21      | 28      | 35      | 42      | 56      | 70       | V     |
| Maximum DC Blocking Voltage  | 20          | 30      | 40      | 50      | 60      | 80      | 100      | V     |
| Maximum Average Forward Rectified Current at Tc=100°C  | 8           |         |         |         |         |         |          | A     |
| Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method) | 150         |         |         |         |         |         |          | A     |
| Maximum Forward Voltage at 4.0A per element  | 0.55        |         | 0.75    |         | 0.85    |         |          | V     |
| Maximum DC Reverse Current at Tc=25°C  | 0.5         |         |         |         |         |         |          | mA    |
| DC Blocking Voltage per element Tc=100°C   | 50          |         |         |         |         |         |          |       |
| Typical Thermal Resistance Note RθJA   | 60          |         |         |         |         |         |          | °C/W  |
| Operating and Storage Temperature Range  | -50 to +125 |         |         |         |         |         |          | °C    |

#### NOTES:


1. Thermal Resistance Junction to Ambient .




**RATING AND CHARACTERISTIC CURVES**




**Fig.1- FORWARD CURRENT DERATING CURVE**




**Fig.2- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC**



**Fig.3- TYPICAL REVERSE CHARACTERISTIC**



**Fig.4- MAXIMUM NON-REPETITIVE SURGE CURRENT**



**Fig.5- TYPICAL JUNCTION CAPACITANCE**