

SCHOTTKY BARRIER RECTIFIERS


VOLTAGE RANGE: 20 --- 100 V
CURRENT: 1.0A

FEATURES

- ◇ Metal-Semiconductor junction with guard ring
- ◇ Epitaxial construction
- ◇ Low forward voltage drop, low switching losses
- ◇ High surge capability
- ◇ For use in low voltage, high frequency inverters free wheeling, and polarity protection applications
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case: JEDEC DO--41, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL- STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.012 ounces, 0.34 grams
- ◇ Mounting position: Any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		SR120	SR130	SR140	SR150	SR160	SR180	SR1A0	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	20	30	40	50	60	80	100	V
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	56	70	V
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	80	100	V
Maximum average forward rectified current 9.5mm lead length, (see fig.1)	$I_{F(AV)}$	1.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ C$	I_{FSM}	40.0							A
Maximum instantaneous forward voltage @ 1.0A (Note 1)	V_F	0.55		0.7		0.85		V	
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	I_R	0.5 10.0							mA
Typical junction capacitance (Note2)	C_J	110							pF
Typical thermal resistance (Note3)	$R_{\theta JA}$	50							°C/W
Operating junction temperature range	T_J	- 55 ---- + 125			- 55 ---- + 150				°C
Storage temperature range	T_{STG}	- 55 ---- + 150							°C

NOTE: 1. Pulse test : 300 μs pulse width, 1% duty cycle.
 2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
 3. Thermal resistance junction to ambient

FIG.1 – FORWARD DERATING CURVE




FIG.2 – PEAK FORWARD SURGE CURRENT




FIG.3 – TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 – TYPICAL JUNCTION CAPACITANCE

