



Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# SS210H-LTP

## **Features**

- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- For Surface Mount Applications
- Low Reverse Current
- High Current Capability
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

## **Maximum Ratings**

- Operating Temperature: -55°C to +175°C
- Storage Temperature: -55°C to +175°C
- Halogen free available upon request by adding suffix "-HF"


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage		Voltage
SS210H-LTP	SS210H	100V	70V	100V

## Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Rectified Forward Current	I <sub>F</sub>	2.0A	T <sub>L</sub> =100°C
Peak Forward Surge Current	I <sub>FSM</sub>	50A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	$V_{\sf F}$	.85V	I <sub>F</sub> = 2.0A;
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	5μA(max) 1μA(typ) 2mA	$T_J = 25^{\circ}C$ $T_J = 25^{\circ}C$ $T_J = 100^{\circ}C$

Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

# 2 Amp Schottky Rectifier 100 Volts



DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.079	.096	2.00	2.44		
В	.050	.064	1.27	1.63		
С	.002	.008	.05	.20		
D	_	.02		.51		
E	.030	.060	.76	1.52		
F	.065	.091	1.65	2.32		
G	.189	.220	4.80	5.59		
Н	.157	.181	4.00	4.60		
J	.090	.115	2.25	2.92		





## Ordering Information:

Device	Packing	
SS210H-LTP	Tape&Reel: 5Kpcs/Reel	

Note: Adding "-HF" suffix for halogen free, eg. SS210H-LTP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.